



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

Medium efficiency air filter

Grades: F5 /F5/ F6/ F6/ F7/ F7/ F8 /F8

Filtration effectiveness:

40%-45%/40%-45%/60%-65%/60%-65%/80%-85%/80%-85%/90%-99%/90%-99%

Size:

595*595*500/495*595*500/595*495*500/495*495*500/595*495*600/595*495*600/595*595*600/595*495*600

air quantity(m/h): 3200/2700/3200/2200/3200/3000/3000/2700

Initial resistance(Pa): 50/50/60/60/105/105/115/115

Pockets: 6/6/6/5/10/8/10/8

Product Description:

Yitong medium efficiency air filter is made of non-woven fabrics and galvanized plate. It can stop the particles at the size of 1-5 microns. The thermal bonded tech is used to improve the leakproofness and reduce the possibility of breakage. It has not only the advantages of high throughput, low resistance and high dirt holding capacity but also can be reusable because it is washable which gives it longer service life.

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years



Performance Feature:

- 1 High temperature resistance and high efficiency
- 2 High capacity, great ability
- 3 Reusable

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

Application:

Medium efficiency air filters are mainly applied for the medium filtration in hospitals, chemical industry, electronic industry, and pharmaceutical industry, which could relieve the workload of the high efficiency filter.

Technical Parameter:

Grades	Filtration effectiveness	Size	air quantity(m/h)	Initial resistance(Pa)	Pockets
F5	40%-45%	595*595*500	3200	50	6
F5	40%-45%	495*595*500	2700	50	6
F6	60%-65%	595*495*500	3200	60	6
F6	60%-65%	495*495*500	2200	60	5
F7	80%-85%	595*495*600	3200	105	10
F7	80%-85%	595*495*600	3000	105	8
F8	90%-99%	595*595*600	3000	115	10
F8	90%-99%	595*495*600	2700	115	8

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

Packing and shipping:



FAQ:

Q: How can we get the quotation of filter cartridges ?

A: Kindly please let us know the specifications, such as the material, length, micron, adapter, apply in which industry.....

Q: What's the minimal quantity order ?

A: 1 piece

Q: How long about your delivery ?

A: The order is always arranged in 10 working days as soon as receiving your payment.

Q: Is customized service available ?

A: Yes, we offer customized service

Q: How about payment terms ?

A: We accept L/C, T/T, Escrow, Paypal or as your requirement

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689