



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

Stainless mesh sintered filter cartridge

Filter media: 304, 316L Stainless steel

Seal ring material: Silicone rubber, EPDM, PTFE

Max. working temperature: $\leq 200^{\circ}\text{C}$

Max. working pressure drop: 300Mpa/23 $^{\circ}\text{C}$

Rating: 1, 2, 5, 10, 20, 50, 75, 100 micron

Length: 210, 250, 350, 500, 750, 1000mm

OD: 47, 65, 76, 86, 100mm

Connector: M20 M65 222 226

Product Description:

YitongSS Sintered Filters are designed to provide high quality particulate Removal in Process Steam together with high flow rate and dirt holding capacity, thereby allowing long system lifetime and cost effective operation. SS Sintered filters are made from fine SS powder is sintered to form filters in cylindrical shape. SS Sintered elements can be cleaned by immersion in dilute hydrochloric acid, ultrasonic bath, clean water or air depending on the type of contamination, which gives it a long service life.

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years



Performance Feature:

- 1,316L Stainless Steel Filter Cartridge
- 2,Exceptionally high Flow Rate
- 3,High Dirt Holding Capacity
- 4,All Welded Construction, NO Leachable
- 5,No Migration, Non Fiber Releasing

Application:

- 1 Steam filtration
- 2 Filtration of the high viscous, strong corrosive and strong polarized liquids
- 3 Filtration of liquids under condition of high temperature and pressure
- 4 Decarburization filtration

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

Technical Parameter:

Cartridge structure	Filter media	304, 316L Stainless steel
	Seal ring material	Silicone rubber, EPDM, PTFE
Working situation	Max. working temperature	≤200°C
	Max. working pressure drop	300Mpa/23°C
Rating	1, 2, 5, 10, 20, 50, 75, 100 micron	
Length	210, 250, 350, 500, 750, 1000mm	
OD	47, 65, 76, 86, 100mm	
Connector	M20 M65 222 226	

Packing and shipping:



Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail: manager@yitong-filter.com

WhatsApp: +86 180 3376 5689

WeChat: +86 180 3376 5689



Yitong Filter Machinery Co., Ltd.

Focusing on providing the most extensive filtration solutions for global customers in 16 years

FAQ:

Q: How can we get the quotation of filter cartridges ?

A: Kindly please let us know the specifications,such as the material,length,micron,adapter,apply in which industry.....

Q: What's the minimal quantity order ?

A: 1 piece

Q:How longabout your delivery ?

A: The order is always arranged in 10 working days as soon as receiving your payment.

Q: Is customized service available ?

A: Yes, we offer customized service

Q: How about payment terms ?

A: We accept L/C, T/T, Escrow, Paypal or as your requirement

Tel: +86 311 6668 5297

Mob: +86 180 3376 5689

Fax: +86 311 6668 5290

E-mail:manager@yitong-filter.com

WhatsApp:+86 180 3376 5689

WeChat: +86 180 3376 5689